

# Schedule of Accreditation

issued by

## United Kingdom Accreditation Service

21 - 47 High Street, Feltham, Middlesex, TW13 4UN, UK

 <p>Accredited to ISO/IEC 17025:2005</p>	<h3>ACS Analysis Ltd</h3> <p><b>Issue No:</b> 014    <b>Issue date:</b> 16 October 2008</p>	
	<p><b>Unit 14A</b>  <b>Blackhill Road West</b>  <b>Holton Heath Trading Park</b>  <b>Poole</b>  <b>Dorset</b>  <b>BH16 6LE</b></p>	<p><b>Contact: Mr D S Faulkner</b>  <b>Tel: +44 (0)1202 628660</b>  <b>Fax: +44 (0)1202 628630</b>  <b>E-Mail: analysis@acsanalysis.co.uk</b>  <b>Website: www.acsanalysis.co.uk</b></p>
<p><b>Testing performed at the above address only</b></p>		

### DETAIL OF ACCREDITATION

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
GEOMEMBRANES	Initial tear resistance (loads from 0 to 2.5 kN)	ASTM D 1004-07
	Density by the density-gradient technique	ASTM D 1505-03
	Carbon black content by the muffle-furnace technique	ASTM D 4218-96 (2001)
	Integrity of field seams - 180° peel strength (loads from 0 to 2.5 kN)	ASTM D 4437-99 ASTM D 413-98 (2002)e1 (Type A)
	Integrity of field seams - shear strength (loads from 0 to 2.5 kN)	ASTM D 4437-99 ASTM D 816-06 (Method B)
	Index puncture resistance (loads from 0 to 2.5 kN)	ASTM D 4833-07
	Nominal thickness	ASTM D 5199-01 (2006)
	Calculation of 2% secant modulus for polyethylene geomembranes	ASTM D 5323-92 (2006)
	Microscopic evaluation of the dispersion of carbon black	ASTM D 5596-03
	Core thickness of textured geomembrane	ASTM D 5994-98 (2003)
Integrity of nonreinforced geomembrane seams - peel testing - shear testing (loads from 0 to 2.5 kN)	ASTM D 6392-08	



2301  
Accredited to  
ISO/IEC 17025:2005

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
21 - 47 High Street, Feltham, Middlesex, TW13 4UN, UK

**ACS Analysis Ltd**  
**Issue No: 014 Issue date: 16 October 2008**

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
GEOMEMBRANES	Tensile properties (loads from 0 to 2.5 kN)	ASTM D 6693-04
	Tensile properties (loads from 0 to 2.5 kN)	ANSI/NSF Modification Standard 54: 1993 Annex A Part 8, based on ASTM D 638-03, using type IV die
	Asperity measurement using a depth gauge	Geosynthetic Research Institute test method GM12
GEOSYNTHETIC CLAY LINERS	Index flux using a flexible wall permeameter	ASTM D 5887-08
	Calculation of hydraulic conductivity using index flux test data	ASTM D 5887-08
	Swell index of clay mineral component	ASTM D 5890-06
	Mass per unit area	ASTM D 5993-99 (2004)
	Peel strength (loads from 0 to 2.5 kN)	Documented In-House Method No 7 : August 2006 based on ASTM D 4632-91 (2003)
GEOTEXTILES	Dynamic perforation test (cone drop test)	BS EN ISO 13433:2006
	Nominal thickness	BS EN ISO 9863-1:2005 ASTM D 5199-01 (2006)
	Mass per unit area	BS EN ISO 9864:2005
	Wide-width tensile test (loads from 0 to 50 kN)	BS EN ISO 10319:1996
	Static puncture test (CBR-Test) (loads from 0 to 50 kN)	BS EN ISO 12236:2006
	Grab breaking load and elongation (loads from 0 to 2.5 kN)	ASTM D 4632-91 (2003)



2301

Accredited to  
ISO/IEC 17025:2005

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
21 - 47 High Street, Feltham, Middlesex, TW13 4UN, UK

**ACS Analysis Ltd**

**Issue No: 014 Issue date: 16 October 2008**

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
SOILS for civil engineering purposes	Moisture content - oven drying method  Density - linear measurement  Permeability in a triaxial cell  Determination of the permeability of clayey soils in a triaxial cell using the accelerated permeability test	BS 1377-2:1990  BS 1377-2:1990  BS 1377-6:1990  Environment Agency R & D Technical Report P1-398/TR/2 : January 2003
END		