


# Schedule of Accreditation

issued by

## United Kingdom Accreditation Service

21 - 47 High Street, Feltham, Middlesex, TW13 4UN, UK

 <b>Accredited to ISO/IEC 17025:2005</b>	<b>Lee Cunningham Partnership</b> <b>Issue No: 006 Issue date: 02 November 2010</b>	
	<b>Riverside House 3 Winnersh Fields Gazelle Close Winnersh Wokingham RG41 5QS</b>	<b>Contact: Mr D Herries Tel: +44 (0)844 847 5370 Fax: +44 (0)844 847 5371 E-Mail: david.herries@caicegroup.co.uk Website: www.lcpacoustics.co.uk</b>

**Testing performed by the Organisation at the locations specified below**

### Locations covered by the organisation and their relevant activities

#### Site activities performed away from the locations listed above:

Location details	Activity	Location code
Any suitable customer premises	Sound insulation tests ie pre-completion testing for Building Regulations Approved Document E: 2003	Site A
Unit 4 Butts Pond Industrial Estate Sturminster Newton Dorset DT10 1AZ	Static Insertion Loss Dynamic Insertion Loss Total Pressure Loss Regenerated Noise of ducted silencers/attenuators	Site B



4241  
Accredited to  
ISO/IEC 17025:2005

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
21 - 47 High Street, Feltham, Middlesex, TW13 4UN, UK

**Lee Cunningham Partnership**  
**Issue No:** 006 **Issue date:** 02 November 2010

Testing performed by the Organisation at the locations specified

DETAIL OF ACCREDITATION

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
Buildings - elements such as partitions, walls, floors,	Field measurement of airborne sound insulation, ie Level Difference and related factors	The Building Regulations 2000 Approved Document E (2003)	Site A
Buildings - floors	Field measurement of impact sound insulation of floors between rooms, ie Impact Sound Pressure Level and related factors	The Building Regulations 2000 Approved Document E (2003)	Site A
Ducted silencers/attenuators	Static Insertion Loss Dynamic Insertion Loss Total Pressure Loss Regenerated Noise of ducted silencers in the range 50 to 10000 Hz in 1/3 or 1/1 octave bands	BS EN ISO 7235: 2009 BS EN ISO 5136: 2009	Site B

END